

CLICK HERE TO CALL US - 660-438-8998 OR CHAT WITH US HERE

- Reliable • Powerful • Smooth
- Heavy Duty • 20" Contact Wheel

**BURR KING®**



98930 Shown  
with optional  
02-8 pedestal

2" x 72"  
Belt Size

**BBA20**  
~  
**THE PRO'S  
CHOICE**

- Up to 6,000 SFPM abrasive belt speed
- 20" 55 duro rubber contact wheel standard
- Uses standard 2" x 72" belts
- Positive belt tracking
- 1.5 HP motor standard
- 120 Volt Single Phase to 575 Volt 3 Phase & multiple horsepower options available
- Fixed height or adjustable height pedestal available
- Articulating arm attachment accessory available
- Multiple durometer contact wheel with plain or serrated face are available on special order

**THE BBA20 FEATURES A 20" CONTACT WHEEL THAT REDUCES THE ANNOYING CHATTER FROM THE JOINT SPLICE AND GIVES A SHALLOW HOLLOW GRIND THAT IS NEARLY FLAT.**



e-catalog

Click or Scan  
the QR Codes  
for more  
information



Videos

ALWAYS WEAR PROTECTIVE EYE, FACE, ARM, LEG AND BODY GEAR WHEN USING ANY GRINDER, POLISHER, BUFFER OR OTHER ROTATING MACHINERY.



**BURR KING**

**BBA20**



*Adding the articulating arm to your BBA20 gives you endless angles and the ability to attach grinding fixtures and jigs.*

Burr King's BBA20 Belt Grinder was the first machine designed with the single intention of giving you the largest contact wheel grinder on the market. The 20" contact wheel allows you to grind with the appearance and function of a flat grind with the ease of a hollow grind. The BBA20's contact wheel is machined from billet aluminum at Burr King's factory in Missouri. The wheel is covered with a 55-60 durometer neoprene for years of trouble free performance. Utilizing an extremely ridged aluminum cast frame this grinder follows in the foot steps of Burr King's legendary 960-272 Knifemaker's Grinder.

## BBA20 BELT GRINDER SPECIFICATIONS

For optional features & specifications consult factory

Abrasive Belt Size	2" x 72"
Horsepower	1.5 HP Standard - Optional motors available
Voltage	120 Volt Single Phase up to 575 3 Phase
Abrasive Belt Speed (up to)	600-6,000 SFPM Variable Speed
Throat Clearance	N/A
Contact Wheel Dimensions	20" x 2" - 1" wheels are available
Contact Wheel Hardness	55 Durometer - Optional durometers available
Belt Tension, Quick Change Assembly	Yes
Positive Belt Tracking Adjustment	Yes
Overall Height x Width x Depth	20" x 20" x 30"
Base Area	13.5" x 16.5"
Adjustable Workrest	Optional Articulating Arm
Construction	Cast Aluminum
Estimated Shipping Weight	75 - 100 lbs
Bench or Pedestal Mounted	Yes



*Add an adjustable pedestal to your BBA20 for a friendly ergonomic grind.*